

AMI 1000

Leak detectors

PFEIFFER 
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP



Scalable

Non-destructive testing, specially designed for lab use as well as inline testing

Deterministic

Quantifiable and repeatable results according to USP <1207> standard

Versatile

Turnkey solution with customized test chambers, adaptable to vials, syringes, blister, intravenous (IV) bags and other non-porous packages

Accessories, spare parts and options

- Customized test chambers
- Calibration gas supply
- Venting gas
- Possibility to use a customer laptop via Ethernet or WiFi connection
- Remote access to data


AMI 1000

Leak detectors

PFEIFFER
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP

Dimensional drawing



AMI 1000	
Sensitivity	Down to 0.4 μm , $2 \cdot 10^{-5}$ mbar $\cdot$ l/s
CDA supply	required for operation
CDA quality	1.3.1 according to ISO 8573-1
CDA pressure	91 - 145 psig / 6.3 - 10 bar rel.
Typical CDA consumption	2 NI/cycle
Calibration gas supply	optional
Calibration gas pressure	91 - 145 psig / 6.3 - 10 bar rel.
Venting gas	optional
Venting gas pressure	0 - 22 psig / 0 - 1.5 bar rel.
Power supply	90 - 250 V AC
Typical power consumption	1200 W
Operating temperature	20 - 25 $^{\circ}\text{C}$
Humidity	30 - 65 %
User interface	10" multi-touch full HD color screen
Software	21 CFR part 11 compliance, PDF GMP test and calibration reports, authentication local or domain (LDAP), optional remote access to data

AMI 1000

Leak detectors

PFEIFFER 
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP

AMI 1000	
Operating system	Windows 10
Network connection	1x LAN (RJ45) WiFi AP
Interfaces	2x USB 3.0 (ext.), 1x HDMI
Sound pressure level	<53 dB(A)
Weight approx.	130 kg
Dimensions (L x W x H)	913 x 558 x 1071 mm

*depending on configuration

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!



CONTACT FORM