

HiPace 300 M

Turbomolecular vacuum pumps

PFEIFFER 
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP



Maintenance-free

Electromagnetic suspension protecting rotor from premature wear, continuous rotor imbalance compensation

Quiet

Low noise and vibration levels

Reliable

Hydrocarbon-free, automatic sensor calibration during operation

Accessories, spare parts and options

- Electrical adapter
- Mains cable
- Connecting cable
- Various fieldbus systems
- Power supply kit and display unit
- Pressure sensor
- Mounting kit
- Safety valve
- Venting accessories
- Power failure venting unit


HiPace 300 M

Turbomolecular vacuum pumps

PFEIFFER
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP

Pumping speed



HiPace 300 M	
Pumping speed for N ₂	255 l/s
Pumping speed for H ₂	170 l/s
Pumping speed for He	215 l/s
Pumping speed for Ar	250 l/s
Compression ratio for N ₂	$1 \cdot 10^{11}$
Compression ratio for H ₂	$5 \cdot 10^5$
Compression ratio for He	$1 \cdot 10^8$
Compression ratio for Ar	$1 \cdot 10^{11}$
Gas throughput at final rotational speed for N ₂	28 hPa l/s
Gas throughput at final rotational speed for Ar	13 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for He	8 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for H ₂	5 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for N ₂	10 hPa l/s
Forevacuum max. for N ₂	20 hPa
Run-up time	2 min
Sound pressure level (EN ISO 2151)	45 dBA

HiPace 300 M

Turbomolecular vacuum pumps

PFEIFFER 
VACUUM+FAB SOLUTIONS

Part of the **BUSCH** GROUP

HiPace 300 M	
Weight approx.	13.1 kg
Communication interfaces standard	RS-485, remote
Mounting orientation	arbitrary
Gas inlet / outlet	DN 100 ISO-K/ISO-F/CF-F / DN 16 ISO-KF

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!



CONTACT FORM