HiPace 800 H

Turbomolecular vacuum pumps

PFEIFFER VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP



High performance

Best compression ratio for light gases, perfectly suited for high and ultra-high vacuum applications

Reliable

Best-in-class hybrid bearing technology, long life cycle, maximum uptime

Quiet

Low noise and vibration levels thanks to patented laser balancing technology

Accessories, spare parts and options

- Electrical adapter
- Mains cable
- Connecting cable
- Various fieldbus systems
- Power supply kit and display unit
- Mounting kit
- Safety valve
- Venting accessories
- Power failure venting unit
- Vibration damper

© Pfeiffer Vacuum


HiPace 800 H

Turbomolecular vacuum pumps

PFEIFFER VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP

Pumping speed



	HiPace 800 H
Pumping speed for N_2	790 l/s
Pumping speed for H_2	580 l/s
Pumping speed for He	700 l/s
Pumping speed for Ar	780 l/s
Compression ratio for N_2	$1 \cdot 10^{13}$
Compression ratio for H_2	$2 \cdot 10^{7}$
Compression ratio for He	$1 \cdot 10^{9}$
Compression ratio for Ar	$1 \cdot 10^{13}$
Gas throughput at final rotational speed for N_2	3.5 hPa l/s
Gas throughput at final rotational speed for H_2	14 hPa l/s
Gas throughput at final rotational speed for He	18 hPa l/s
Gas throughput at final rotational speed for Ar	2 hPa l/s
Forevacuum max. for N_2	22 hPa
Run-up time	2 min
Sound pressure level (EN ISO 2151)	50 dBA
Weight approx.	12.8 kg

HiPace 800 H

Turbomolecular vacuum pumps

PFEIFFER VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP

	HiPace 800 H
Communication interfaces standard	RS-485, remote
Mounting orientation	arbitrary
Gas inlet / outlet	DN 200 ISO-K/ISO-F/CF-F / DN 25 ISO-KF /G 1/4"

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!

CONTACT FORM

© Pfeiffer Vacuum