HiPace 1200/1500

Turbomolecular vacuum pumps

PFEIFFER
VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP



High performance

High pumping speed, excellent compression for light gases

Flexible

Extensive portfolio, standard accessories and communication tools

Robust

Best-in-class hybrid bearing technology, maximum uptime, nickel-coated surfaces for corrosive applications

Accessories, spare parts and options

- Electrical adapter
- Mains cable
- Connecting cable
- Display unit
- Safety and mounting kits
- Venting accessories
- Sealing gas accessories

© Pfeiffer Vacuum


HiPace 1200/1500

Turbomolecular vacuum pumps


PFEIFFER VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP

Pumping speed



Pumping speed



	HiPace 1200	HiPace 1500
Pumping speed for N_2	1250 l/s	1400 l/s
Pumping speed for H_2	1100 l/s	1150 l/s
Pumping speed for He	1300 l/s	1350 l/s
Pumping speed for Ar	1200 l/s	1350 l/s
Compression ratio for N_2	$1 \cdot 10^{8}$	$1 \cdot 10^{8}$
Compression ratio for H_2	$6 \cdot 10^{3}$	$6 \cdot 10^{3}$
Compression ratio for He	$6 \cdot 10^{4}$	$6 \cdot 10^{4}$
Compression ratio for Ar	$1 \cdot 10^{8}$	$1 \cdot 10^{8}$
Gas throughput at final rotational speed for N_2	20 hPa l/s	20 hPa l/s
Gas throughput at final rotational speed for H_2	30 hPa l/s	30 hPa l/s
Gas throughput at final rotational speed for He	30 hPa l/s	30 hPa l/s
Gas throughput at final rotational speed for Ar	11 hPa l/s	11 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for He	15 hPa l/s	15 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for H_2	8 hPa l/s	8 hPa l/s
Gas throughput at 0.1 hPa HV-pressure for N_2	26 hPa l/s	26 hPa l/s
Forevacuum max. for N_2	2 hPa	2 hPa

HiPace 1200/1500

Turbomolecular vacuum pumps

PFEIFFER VACUUM+FAB SOLUTIONS

Part of the BUSCH GROUP

	HiPace 1200	HiPace 1500
Run-up time	2.5 min	2.5 min
Sound pressure level (EN ISO 2151)	50 dBA	50 dBA
Weight approx.	30.5 kg	31.2 kg
Communication interfaces standard	RS-485, remote	RS-485, remote
Mounting orientation	0° (HV flange top) – 90° / 90° – 180° (HV flange bottom)	0° (HV flange top) – 90° / 90° – 180° (HV flange bottom)
Gas inlet / outlet	DN 200 ISO-K/ISO-F/CF-F / DN 40 ISO-KF	DN 250 ISO-K/ISO-F/CF-F / DN 40 ISO-KF

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!

CONTACT FORM

© Pfeiffer Vacuum